

PART NUMBER - VALVE SELECTION

Series	Size	-	Base Code	Body	Ball/ Stem	Seats	Seals	-	Service Mod	Ball Mod	Special Features
15	0400	-	11002	S	S	J	G	-	N	N	
1	2	-	3	4	5	6	7	-	8	9	-10

Example: 150400-11002SSJG-NN = 4" F30, Full Port, ANSI 300 RF Flanged Ends, Stainless Steel Body, Ball and Stem, TFM 1600 Seats, Graphite Seals.

1	Series	15	Flanged Series - Floating Ball Valves	Website Link
---	--------	----	---------------------------------------	------------------------------

2	Size	0050	1/2"	(Full Port Only)	0200	2"		0600	6"
		0075	3/4"	(Full Port Only)	0250	2-1/2"	(Full Port Only)	0800	8"
		0100	1"		0300	3"		1000	10"
		0150	1-1/2"		0400	4"		1200	12"

-	-
---	---

3	Base Code (Model)	11000	F15 - Full Port - ANSI 150 RF Flanged Ends	11001	RF15 - Standard Port - ANSI 150 RF Flanged Ends
		11002	F30 - Full Port - ANSI 300 RF Flanged Ends	11021	RF30 - Standard Port - ANSI 300 RF Flanged Ends
		11F00	F15 - Full Port - ANSI 150 RF - NSF 61	11F01	RF15 - Standard Port - ANSI 150 RF - NSF 61
		11F02	F30 - Full Port - ANSI 300 RF - NSF 61	11F21	RF30 - Standard Port - ANSI 300 RF - NSF 61
			F15 / F30 Website Link	F15 / F30 Brochure	RF15 / RF30 Website Link

4	Body	S	316 Stainless Steel	A	Alloy 20
		C	WCB Carbon Steel	?	Special Materials (Consult Factory)

5	Ball & Stem	S	316 Stainless Steel Ball with 316 Stainless Steel Stem	D	316 Stainless Steel Ball with 17-4 SS Stem
				A	Alloy 20 Ball and Alloy 20 Stem

6	Seats	J	TFM 1600	U	UHMWPE
		K	Tek-Fil	P	PEEK*
		R	RPTFE	T	PTFE
		F	TFM (NSF 61 Registered)		

7	Seals	G	Graphite	U	UHMWPE
		R	RPTFE	K	Tek-Fil
		J	TFM 1600	T	PTFE
		F	PTFE (NSF 61 Registered)		

-	-
---	---

8	Service Modification	N	None	X	Oxygen Cleaning
		C	General Cleaning	M	NACE MRO 175 2003 (Upgraded Bolting - F15/F30)
		F	NSF 61 Certification and Tagging		

9	Ball Modification	N	None	H	Vented Ball

-	-
---	---

10	Special Features (Optional)	0001	Cavity Fillers Polished to 30-35 Ra	0031	Polished 10-15 Ra	0055	Special Trust Washer Material Consult Factory
		0009	Ra	0210	Polished 8-12 Ra	????	
		0032	Polished to 20-25 Ra				

NOTES:

15 Series Valves come standard with a Lockable Lever. Recommended to add a Gear Operator for 6" Full Port and up. Not all sizes are available in Standard Port (RF15/RF30) Models - See price pages

*17-4 Stem is Required when using PEEK seats

Stainless Steel Spiral Wound Graphite Body Seal is standard on F15/F30 unless otherwise requested. Flat Face Flanged Ends or RTJ Flanged Ends are available on request.

General Cleaning per Flow-Tek WI-125 (solvent method) & Bagged meets ASME BPE-2002A Cavity Fillers only Available in F15 and F30 Models

Special Materials of Construction are available on request.